


## Product Datasheet

### RPU5000



#### Main

Family	Distribution blocks quick
Version	1 Pole
Code	RPU5000
Reference	RPU 80-S-14-B
Number per package	10
Weight (g)	48
In (A)	80
A (mm)	53
B (mm)	47
C (mm)	24
D (mm)	12

## Technical Features

### Materials

Insulating block: PA 6, UL-94 V0, grey RAL 7035

Conduction block: Brass

Screws: steel

Terminals: Spring steel

### Protection grade IP20

**Maximum working temperature: 125 °C**

### Halogen free

### Cable tightening:

For inputs: screws

For outputs: spring steel system with copper contact

**Direct fitting on DIN rails or plate using 4 screws M4**

**Compliant with standard EN 60947-7-1**

## Technical Data

Type	80 A	No.	Stripped wire (mm <sup>2</sup> )	Wire with ferrule (mm <sup>2</sup> )	Tightening Torque (Nm)	Screw	Ui (V)
1 Pole, 80 A	IN →	2	1.5 ÷ 25	1.5 ÷ 16	2.5	M8	1000
	← OUT	14	0.5 ÷ 4	0.5 ÷ 4	-	-	



## Advantages

Extremely easy wiring

Output with spring tightening

Highly reliable and stable connection with:

- Rigid stripped cable
- Cable with ferrule

Please contact Teknomega for non-specified tolerances.