

## Product Datasheet

### TTR1015



The copper braid is used as a super flexible conductor for all electric connection requirements, including power, earthing and equipotential connections.

It results from the use of a number of standard wires with diameter of 0.20 mm, twined together to form a cord.

More cords twined together can produce a small cross-sectioned braid or further secondary cords which, twined again, make it possible to get the desired cross-section.

#### Main

Family	Copper braids in coils
Version	Round braids
Code	TTR1015
Reference	TTR 20-25
Type	Red copper
Length (m)	25
Weight (kg/m)	0.25
Current (A)*	152
Sect. (mm <sup>2</sup> )	25
Diameter Ø (mm)	8.0
Minimum bending radius (mm)	32

\* Current calculated with a temperature rise  $\Delta T=35$  °C respect to a reference room temperature of 35 °C

### Technical Features

**Material:** red copper Cu-ETP UNI EN 13602

Standard wire  $\varnothing$  0.20 mm

**Resistivity:** 0.0172  $\Omega$  mm<sup>2</sup>/m

### Round type copper braids

Made from tightly interwoven cords until they become a full round section.

It is used for power and mass connections, and, when suitably insulated, as an alternative to the cables. In that case, compared to insulated cables, with the same cross-section, it allows more current density and, most of all, extraordinary flexibility.

Please contact Teknomega for non-specified tolerances.